

REGULAR ENGINES

SINGLE STAGE ENGINES (GREEN LABEL)

Prod. No.	Engine Type	Prices 3 for	Total Impulse		Time Delay (±15%)	Max. Lift Wt. oz./g	Max. Thrust lb./N	Thrust Duration	Initial Weight		Propellant Weight	
			lb.-sec. ¹	N-sec. ²					oz.	g	oz.	g
1593	1/2A6-2*		0.28	1.25	2 sec.	2.5/ 70.8	2.88/12.8	0.20 sec.	0.53	15.0	0.055	1.56
1598	A8-3		0.56	2.50	3 sec.	4.0/113.2	3.00/13.3	0.32 sec.	0.57	16.2	0.110	3.12
1601	B4-2		1.12	5.00	2 sec.	4.0/113.2	3.00/13.3	1.20 sec.	0.70	19.8	0.294	8.33
1602	B4-4		1.12	5.00	4 sec.	3.5/ 99.1	3.00/13.3	1.20 sec.	0.74	21.0	0.294	8.33
1605	B6-2		1.12	5.00	2 sec.	4.5/127.4	3.00/13.3	0.83 sec.	0.68	19.3	0.220	6.24
1606	B6-4		1.12	5.00	4 sec.	4.0/113.2	3.00/13.3	0.83 sec.	0.71	20.1	0.220	6.24
1620	B8-5*		1.12	5.00	5 sec.	5.0/141.5	5.00/22.2	0.60 sec.	0.68	19.3	0.220	6.24
1617	C5-3*		2.25	10.00	3 sec.	8.0/226.4	5.00/22.2	2.10 sec.	0.90	25.5	0.450	12.70
1613	C6-3		2.25	10.00	3 sec.	4.0/113.2	3.00/13.3	1.70 sec.	0.88	24.9	0.440	12.48
1614	C6-5		2.25	10.00	5 sec.	4.0/113.2	3.00/13.3	1.70 sec.	0.91	25.8	0.440	12.48

UPPER STAGE ENGINES or single stage if used in a very light rocket (PURPLE LABEL)

1599	A8-5		0.56	2.50	5 sec.	2.0/ 56.6	3.00/13.3	0.32 sec.	0.62	17.6	0.110	3.12
1604	B4-6		1.12	5.00	6 sec.	1.5/ 42.5	3.00/13.3	1.20 sec.	0.78	22.1	0.294	8.33
1607	B6-6		1.12	5.00	6 sec.	2.0/ 56.6	3.00/13.3	0.83 sec.	0.78	22.1	0.220	6.24
1615	C6-7		2.25	10.00	7 sec.	2.5/ 70.8	3.00/13.3	1.70 sec.	0.95	26.9	0.440	12.48

BOOSTER ENGINES (RED LABEL)

1608	B6-0		1.12	5.00	none	4.0/113.2	3.00/13.3	0.80 sec.	0.58	16.4	0.220	6.24
1616	C6-0		2.25	10.00	none	4.0/113.2	3.00/13.3	1.68 sec.	0.80	22.7	0.440	12.48